

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK

DRILL ☒

DEEPEN ☐

PLUG BACK ☐

b. TYPE OF WELL

OIL
WELL ☒

GAS
WELL ☐

OTHER

SINGLE
ZONE ☒

MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

Wildrose Resources Corporation

PH: 303-770-6566

3. ADDRESS OF OPERATOR

4949 South Albion Street, Littleton, CO 80121

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface

1980' FSL & 1980' FEL (NW $\frac{1}{4}$ SE $\frac{1}{4}$)

At proposed prod. zone

Same

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE

11 miles SE of Myton, Utah

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drlg. unit line, if any)

600'

16. NO. OF ACRES IN LEASE

1447.3

17. NO. OF ACRES ASSIGNED
TO THIS WELL

40

18. DISTANCE FROM PROPOSED LOCATION*

TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

1462'

19. PROPOSED DEPTH

6200'

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

4932' GR

22. APPROX. DATE WORK WILL START*

April 1, 1997


23.

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12-1/4"	8-5/8"	24#, J-55	300'	225 sx
7-7/8"	5-1/2"	15.5#, J-55	6200'	800 sx

SEE ATTACHED EXHIBITS: A - Surveyors Plat E - Access Road Map
B - 10 Point Plan F - Production Facilities
C - BOP Diagram G - Existing Wells Map
D - 13 Point Surface Use Program H - Pit & Pad Layout, Cuts & Fills,
Cross Sections, Rig Layout

CONFIDENTIAL



IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

Kerry J. Kattenbach

TITLE

Vice President

DATE

February 21, 1997

(This space for Federal or State office use)

PERMIT NO.

43-047-32846

APPROVAL DATE

APPROVED BY

John R. Byn

TITLE

Petroleum Engineer

DATE


4/21/97

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions On Reverse Side

WILDROSE RESOURCES CORP.
WELL LOCATION PLAT
FEDERAL #33-26

LOCATED IN THE NW1/4 OF THE SE1/4 OF
 SECTION 26, T8S, R18E, S.L.B.&M.




SCALE: 1" = 1000'

LEGEND AND NOTES

- ◇ ORIGINAL MONUMENTS FOUND AND USED BY THIS SURVEY.

THE GENERAL LAND OFFICE (G.L.O.) PLAT WAS USED FOR REFERENCE AND CALCULATIONS AS WAS THE U.S.G.S. QUADRANGLE MAP.

THIS SURVEY WAS PERFORMED USING GLOBAL POSITIONING SYSTEM (GPS) PROCEDURES AND EQUIPMENT.




SURVEYOR'S CERTIFICATE

I HEREBY CERTIFY THAT THIS PLAT WAS PREPARED FROM FIELD NOTES OF AN ACTUAL SURVEY PERFORMED BY ME, DURING WHICH THE SHOWN MONUMENTS WERE FOUND OR ESTABLISHED.

Jerry D. Allred
 JERRY D. ALLRED, REGISTERED LAND SURVEYOR,
 CERTIFICATE NO. 148951 (UTAH)

Exhibit A



JERRY D. ALLRED & ASSOCIATES
 SURVEYING AND ENGINEERING CONSULTANTS

121 NO. CENTER ST.--P.O. BOX 975
 DUCHESNE, UTAH 84021
 (801)-738-5352

14 FEB 1997

83-123-030

EXHIBIT B

WILDROSE RESOURCES CORPORATION
FEDERAL #33-26
LEASE #U-36442
NW/SE SECTION 26, T8S, R18E
UINTAH COUNTY, UTAH

TEN POINT COMPLIANCE PROGRAM OF APPROVAL OF OPERATIONS

1. The Geologic Surface Formation

The surface formation is the Uintah (Tertiary).

2. Estimated Tops of Important Geologic Markers

Green River	1700'
Wasatch Tongue of Green River	6100'
Total Depth	6200'

3. Estimated Depths of Anticipated Water, Oil, Gas or Minerals

No water bearing zones are anticipated

Green River 4000' - 6200' Oil

4. The Proposed Casing Program

<u>HOLE</u>	<u>INTERVAL</u>	<u>LENGTH</u>	<u>SIZE(OP)</u>	<u>WEIGHT, GRADE, JOINT</u>	<u>NEW OR USED</u>
12.25"	0 - 300'	300'	8-5/8"	24# J-55 ST&C	New
7-7/8"	0 - 6200'	6200'	5-1/2"	15.50# J-55 ST&C	New

Cement Program -

Surface Casing: 225 sacks Class "G" plus 2% CaCl₂

Production Casing: 200 sacks Lite Cement and 600 sacks Class "G" with additives

5. The Operator's Minimum Specifications for Pressure Control

EXHIBIT "C" is a schematic diagram of the blowout preventer equipment. A 2M system will be used. The blind rams and the pipe

Accessories to BOP will include an upper kelly cock, floor safety valve, drill string BOP and choke manifold with pressure rating equivalent to the BOP stack.

Mud system will be 2% KCl water with adequate stocks of sorptive agents on site to handle possible spills of fuel and oil on the surface. Heavier muds will be available to be added if pressure requires.

<u>DEPTH</u>	<u>TYPE</u>	<u>WEIGHT #/gal</u>	<u>VISCOSITY sec/qt</u>	<u>FLUID LOSS cc</u>	<u>PH</u>
0-4000'	Air/ Foam	8.4 - 8.6	28 - 30	NC	--
4000- 6200'	2% KCl Water	8.6 - 8.8	30 - 34	NC	9.0

- a) An upper kelly cock will be kept in the string.
- b) A float will be used at the bit.
- c) A mud logging unit will not be used. Mud system will be visually monitored.
- d) A stabbing valve will be on the floor to be stabbed into the drill pipe when kelly is not in the string.

- a) No Drill Stem Tests will be run.
- b) The Logging Program: Dual Later Log 300' - T.D.
Formation Density-CNL 4000' - T.D.
- c) No coring is anticipated.
- d) Stimulation procedures will be determined after evaluation of logs. If treatment is indicated, appropriate Sundry Notice will be submitted for approval.

9. Any Anticipated Abnormal Pressures or Temperatures

No abnormal pressures or temperatures have been noted or reported in wells drilled in the area nor at the depths anticipated in this well. Bottom hole pressure expected is 1500 psi + or -.

No hydrogen sulfide or other hazardous fluids or gases have been found, reported or known to exist at these depths in the area.

10. Anticipated Starting Date and Duration of the Operations.

The anticipated starting date is April 1, 1997. Operations will cover approximately 10 days for drilling and 14 days for completion.

Hazardous Chemicals

No chemicals subject to reporting under SARA title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported or disposed of annually in association with the drilling of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported or disposed of in association with the drilling of this well.

EXHIBIT C
BOP DIAGRAM





EXHIBIT D

WILDROSE RESOURCES CORPORATION
FEDERAL #33-26
LEASE #U-36442
NW/SE SECTION 26, T8S, R18E UINTAH COUNTY, UTAH

Thirteen Point Surface Use Program

Multipoint Requirements to Accompany APD

1. Existing Roads

- A. The proposed well site and elevation plat is shown on Exhibit A.
- B. From Fort Duchesne go south 6 miles to bridge. Go across bridge and follow Leland Bench road 10.0 miles. Turn left to the northeast 1/3 mile to location.
- C. See Exhibit E for access roads.
- D. There are no plans for improvement of existing roads. Roads will be maintained in present condition.

2. Planned Access Roads - (Newly Constructed)

- A. Length - 2100 feet.
- B. Width - 30' right of way with 18' running surface maximum.
- C. Maximum grades - 2%
- D. Turnouts - N/A
- E. Drainage design - Barrow ditches and water turnouts as required.
- F. Culverts, bridges, cuts and fills - None.
- G. Surfacing material (source) - from location and access road.
- H. Gates, cattle guards and fence cuts - None.

All travel will be confined to existing access road rights of way.

Access roads and surface disturbing activities will conform to standards outlined in the Bureau of Land Management and Forest

Service publication: Surface Operating Standards for Oil and Gas Exploration and Development, (1989).

The road shall be upgraded to meet the standards of the anticipated traffic flow and all weather road requirements. Construction/ upgrading shall include ditching, draining, graveling, crowning, and capping the roadbed as necessary to provide a well constructed safe road. Prior to upgrading, the road shall be cleared of any snow cover and allowed to dry completely. Traveling off the 30 foot right of way will not be allowed. Road drainage crossings shall be of the typical dry creek drainage crossing type. Crossings shall be designed so they will not cause siltation or accumulation of debris in the drainage crossing nor shall the drainages be blocked by the roadbed. Erosion of drainage ditches by runoff water shall be prevented by diversion water off at frequent intervals by means of cutouts. Upgrading shall not be allowed during muddy conditions. Should mud holes develop, they shall be filled in and detours around them avoided.

A Right of Way application is not needed.

3. Location of Existing Wells Within a 1 Mile Radius

See Exhibit G

- A. Water wells - none.
- B. Abandoned wells - two.
- C. Temporarily abandoned wells - none.
- D. Disposal wells - none.
- E. Drilling wells - none.
- F. Producing wells - eleven.
- G. Shut-in wells - one.
- H. Injection wells - one.

4. Location of Existing and/or Proposed Facilities

- A. On well pad - See Exhibit F for all production facilities to be used if well is completed as a producing oil well.
- B. Off well pad - N/A

If a tank battery is constructed on this lease, the battery or the well pad will be surrounded by a dike of sufficient capacity to contain, at a minimum, the entire content of the largest tank within the battery, unless more stringent protective requirements

are deemed necessary by the authorized officer.

Tank battery will be placed on the NE corner of the location.

All permanent (on site for six months or longer) structures constructed or installed (including pumping units) will be painted a flat, non-reflective, earthtone color to match one of the standard environmental colors, as determined by the Rock Mountain Five state Interagency Committee. All facilities will be painted within 6 months of installation. Facilities required to comply with O.S.H.A. (Occupational Safety and Health Act) will be excluded.

The required paint color is desert brown, 10YR.

If at any time the facilities located on public land and authorized by the terms of the lease are no longer included in the lease (due to a contraction in the unit or other lease or unit boundary change), BLM will process a change in authorization to the appropriate statute. The authorization will be subject to appropriate rental or other financial obligation as determined by the authorized officer.

5. Location and Type of Water Supply

- A. Water supply will be from Water Permit #43-1721 (Joe Shields spring).
- B. Water will be trucked across existing roads to location.
- C. No water wells to be drilled on lease.

6. Source of Construction Materials

- A. Native materials on lease will be used.
 - B. From Federal land.
 - C. N/A.
- A minerals material application is not required.

7. Methods for Handling Waste Disposal

- A.
 - 1) Drill cuttings will be buried in the reserve pit.
 - 2) Portable toilets will be provided for sewage.
 - 3) Trash and other waste material will be contained in a

trash cage and hauled away to an approved disposal site at the completion of the drilling activities.

4) Salts - if any will be disposed of.

5) Chemicals - if any will be disposed of.

B. Drilling fluids will be handled in the reserve pit. Any fluids produced during testing operations will be collected in a test tank. If a test tank is not available during drilling, fluids will be handled in the reserve pit. Any oil in the reserve pit will be removed.

Burning will not be allowed. All trash must be contained in trash cage and hauled away to an approved disposal site at the completion of drilling activities.

The reserve pit shall be constructed so as not to leak, break, or allow discharge.

A plastic nylon reinforced liner will be used. It will be a minimum of 12 mil thickness with sufficient bedding (either straw or dirt) to cover any rocks. The liner will overlap the pit walls and be covered with dirt and/or rocks to hold it in place. No trash, scrap pipe, etc., that could puncture the liner will be disposed of in the pit. More stringent protective requirements may be deemed necessary by the A.O.

After first production, produced waste water will be confined to a lined pit or storage tank for a period not to exceed 90 days. During the 90 day period, in accordance with Onshore Order No. 7, an application for approval of a permanent disposal method and location, along with required water analysis, shall be submitted for the AO's approval. Failure to file an application within the time allowed will be considered an incident of noncompliance.

8. Ancillary Facilities

A. Camp facilities or airstrips will not be required.

9. Well Site Layout

A. See Exhibit H.

B. See Exhibit H.

C. See Exhibit H.

The reserve pit will be located on the north side of the location.

The flare pit will be located downwind of the prevailing wind direction on the east side of the location a minimum of 100 feet

from the well head and 30 feet from the reserve pit fence.

Topsoil - will be stored along the south side of the location.

Access to the well pad will be from the south.

Fencing Requirements

All pits will be fenced according to the following minimum standards:

a. 39-inch net wire shall be used with at least one strand of barbed wire on top of the net wire (barbed wire is not necessary if pipe or some type of reinforcement rod is attached to the top of the entire fence).

b. The net wire shall be no more than 2-inches above the ground. The barbed wire shall be 3-inches above the net wire. Total height of the fence shall be at least 42-inches.

c. Corner posts shall be cemented and/or braced in such a manner to keep the fence tight at all times.

d. Standard steel, wood, or pipe posts shall be used between the corner braces. Maximum distance between any two posts shall be no greater than 16 feet.

e. All wire shall be stretched, by using a stretching device, before it is attached to the corner posts.

The reserve pit fencing will be on three sides during drilling operations and on the fourth side when the rig moves off the location. Pits will be fenced and maintained until clean-up.

10. Plans for Restoration of Surfaces

A. Producing Location:

Immediately upon well completion, the location and surrounding area will be cleared of all debris, materials, trash and junk not required for production.

Immediately upon well completion, any hydrocarbons on the pit shall be removed in accordance with 43 CFR 3162.7-1.

If a plastic nylon reinforced liner is used, it shall be torn and perforated before backfilling of the reserve pit.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the

approximate natural contours. The reserve pit will be reclaimed within 120 days from the date of well completion. Before any dirt work takes place, the reserve pit must have all fluids and hydrocarbons removed and all cans, barrels, pipe, etc., will be removed.

The BLM will be contacted for required seed mixture.

B. Dry Hole/ Abandoned Location:

At such time as the well is plugged and abandoned, the operator will submit a subsequent report of abandonment and BLM will attach the appropriate surface rehabilitation conditions of approval.

11. Surface Ownership

Access Road: Federal
Location: Federal

12. Other Additional Information

A. The operator is responsible for informing all persons in the area who are associated with this project that they will be subject to prosecution for knowingly disturbing historic or archaeological sites, or for collecting artifacts. If historic or archaeological materials are uncovered during construction, the operator is to immediately stop work that might further disturb such materials, and contact the authorized officer (AO). Within five working days the AO will inform the operator as to:

- Whether the materials appear eligible for the National Register of Historic Places;

- The mitigation measures the operator will likely have to undertake before the site can be used (assuming in situ preservation is not necessary); and

- A time frame for the AO to complete an expedited review under 36 CFR 800.11 to confirm, through the State Historic Preservation Officer, that the findings of the AO are correct and that mitigation is appropriate.

If the operator wishes, at any time, to relocate activities to avoid the expense of mitigation and/or the delays associated with this process, the AO will assume responsibility for whatever recordation and stabilization of the exposed materials may be required. Otherwise, the operator will be responsible for mitigation costs. The AO will provide technical and procedural guidelines for the conduct of mitigation. Upon verification from the AO that required mitigation has been completed, the operator will then be allowed to resume construction.

B. The operator will control noxious weeds along rights-of-way for roads, pipelines, well sites, or other applicable facilities. A list of noxious weeds may be obtained from the BLM, or the appropriate County Extension Office. On BLM administered land it is required that a Pesticide Use Proposal shall be submitted, and given approval, prior to the application of herbicides or other pesticides or possible hazardous chemicals.

C. Drilling rigs and/or equipment used during drilling operations on this wellsite will not be stacked or stored on Federal Lands after the conclusion of drilling operations or at any other time without BLM authorization. However, if BLM authorization is obtained, it is only a temporary measure to allow time to make arrangements for permanent storage on commercial facilities. (The BLM does not seek to compete with private industry. There are commercial facilities available for stacking and storing drilling rigs.)

Additional Surface Stipulations

Reclamation of unused disturbed areas on the well pad/access road no longer needed for operations, such as cut slopes, and fill areas will be accomplished by grading, leveling and seeding as recommended by the Authorized Officer.

13. Lessee's or Operators Representative and Certification Representative

Kary J. Kaltenbacher
Wildrose Resources Corporation ..
4949 South Albion Street
Littleton, CO 80121
Telephone: 303-770-6566

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved plan of operations, and any applicable Notice to Lessees. The operator is fully responsible for the actions of his sub-contractors. A copy of these conditions will be furnished to the field representative to insure compliance.

A complete copy of the approved APD and ROW grant, if applicable, shall be on location during construction of the location and drilling activities.

The operator or his/her contractor shall contact the BLM Office at (801) 789-1362 forty eight (48) hours prior to construction activities.

The BLM Office shall be notified upon site completion prior to moving on the drilling rig.


Self-Certification Statement:

Please be advised that Wildrose Resources Corporation is considered to be the operator of Federal Well No. 33-26, NW/4 SE/4 of Section 26, Township 8 South, Range 18 East; Lease Number U-36442; Uintah County, Utah; and is responsible for the operations conducted upon the leased lands. Bond coverage is provided by Statewide Oil and Gas Bond No. 229352, Allied Mutual Insurance Company, approved by the BLM effective October 26, 1987.

Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which currently exist; that the statements made in this plan are true and correct to the best of my knowledge; and, that the work associated with the operations proposed here will be performed by Wildrose Resources Corporation and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Date 2/21/97


Kary J. Kaltenbacher
Vice President

Onsite Date: February 20, 1997


Participants on Joint Inspection

Kary J. Kaltenbacher
Stan Olmstead
Tom Dabbs

Wildrose Resources Corporation
BLM
BLM

CONFIDENTIAL STATEMENT

WILDROSE RESOURCES CORPORATION, AS OPERATOR, REQUESTS THAT ALL INFORMATION RELATED TO THIS WELL BE HELD TIGHT FOR THE MAXIMUM PERIOD ALLOWED BY FEDERAL AND STATE REGULATIONS.



TOPOGRAPHIC
MAP "A"




WILDROSE RESOURCES CORP.

FEDERAL #33-26
SECTION 26, T8S, R18E, S.L.B.&M.

Exhibit 'E-1'

15 Feb '97

83-123-030



TOPOGRAPHIC
MAP "B"
SCALE: 1"=2000'



WILDROSE RESOURCES CORP.

FEDERAL #33-26
SECTION 26, T8S, R18E, S.L.B.&M.

Exhibit 'E-2'

15 Feb '97

83-123-030

PROPOSED PRODUCTION FACILITY DIAGRAM

VALVE DESCRIPTION		
	DURING PROD.	DURING SALES
VALVE #1	CLOSED	OPEN
VALVE #2	OPEN	CLOSED
VALVE #3	CLOSED	OPEN
VALVE #4	OPEN	CLOSED
VALVE #5	CLOSED	CLOSED
VALVE #6	CLOSED	CLOSED
VALVE #7	CLOSED	OPEN

DIKE









Exhibit 'F'



WILDROSE RESOURCES CORP.
WELL LAYOUT PLAT
FEDERAL #33-26

LOCATED IN THE NW1/4 OF THE SE1/4 OF SECTION 26,
TOWNSHIP 8 SOUTH, RANGE 18 EAST, S.L.B.&M.



APPROXIMATE QUANTITIES

CUT: 3800 CU. YDS. (INCLUDES PIT)
FILL: 700 CU. YDS.

14 FEB 1997

83-123-030

Exhibit 'H'

JERRY D. ALLRED & ASSOCIATES
SURVEYING AND ENGINEERING CONSULTANTS

121 NORTH CENTER STREET
P.O. BOX 975
DUCHESTER, UTAH 84021
(801) 738-5352

WORKSHEET
APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 02/24/97

API NO. ASSIGNED: 43-047-32846

WELL NAME: FEDERAL 33-26
OPERATOR: WILDROSE RESOURCES (N9660)

PROPOSED LOCATION:
NWSE 26 - T08S - R18E
SURFACE: 1980-FSL-1980-FEL
BOTTOM: 1980-FSL-1980-FEL
UINTAH COUNTY
EIGHT MILE FLAT NORTH FIELD (590)

LEASE TYPE: FED
LEASE NUMBER: U - 36442

PROPOSED PRODUCING FORMATION: GRRV

INSPECT LOCATION BY: / /

TECH REVIEW	Initials	Date
Engineering		
Geology		
Surface		

RECEIVED AND/OR REVIEWED:

☒ Plat
☒ Bond: Federal ☒ State ☐ Fee ☐
(Number 229352)
☒ Potash (Y/N)
☒ Oil shale (Y/N)
☒ Water permit
(Number 43-1721)
☒ RDCC Review (Y/N)
(Date: _____)


LOCATION AND SITING:

____ R649-2-3. Unit: _____
☒ R649-3-2. General.
____ R649-3-3. Exception.
____ Drilling Unit.
____ Board Cause no: _____
____ Date: _____

COMMENTS: _____

STIPULATIONS: _____

OPERATOR: WILDROSE (N9660)
FIELD: EIGHT MILE FLAT NORTH (590)
SEC. TWP. RNG. 26, 8S 18E
COUNTY: UINTAH
UAC: R649-3-2



PREPARED:
DATE: 26-FEB-97



State of Utah
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

Michael O. Leavitt
Governor

Ted Stewart
Executive Director

James W. Carter
Division Director

1594 West North Temple, Suite 1210

Box 145801

Salt Lake City, Utah 84114-5801

801-538-5340

801-359-3940 (Fax)

801-538-7223 (TDD)

April 21, 1997

Wildrose Resources Corporation
4949 South Albion Street
Littleton, Colorado 80121

Re: Federal 33-26 Well, 1980' FSL, 1980' FEL, NW SE, Sec. 26,
T. 8 S., R. 18 E., Uintah County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann. 40-6-1 et seq., Utah Administrative Code R649-3-1 et seq., and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-047-32846.

Sincerely,

Lowell P. Braxton
Deputy Director

lwp

Enclosures

cc: Uintah County Assessor

Bureau of Land Management, Vernal District Office

Operator: Wildrose Resources Corporation
Well Name & Number: Federal 33-26
API Number: 43-047-32846
Lease: U-36442
Location: NW SE Sec. 26 T. 8 S. R. 18 E.

Conditions of Approval

1. General

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for Permit to Drill.

2. Notification Requirements

Notify the Division within 24 hours following spudding the well or commencing drilling operations. Contact Jimmie Thompson at (801) 538-5336.

Notify the Division prior to commencing operations to plug and abandon the well. Contact John R. Baza (801) 538-5334 or Mike Hebertson at (801) 538-5333.

3. Reporting Requirements

All required reports, forms and submittals shall be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK

DRILL ☒

DEEPEN ☐

PLUG BACK ☐

b. TYPE OF WELL

OIL
WELL ☒

GAS
WELL ☐

OTHER

SINGLE
ZONE ☒

MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

Wildrose Resources Corporation

PH: 303-770-6566

3. ADDRESS OF OPERATOR

4949 South Albion Street, Littleton, CO 80121

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface

1980' FSL & 1980' FEL (NW $\frac{1}{4}$ SE $\frac{1}{4}$)

At proposed prod. zone
Same

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

11 miles SE of Myton, Utah

10. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drig. unit line, if any)

600'

16. NO. OF ACRES IN LEASE

1447.3

17. NO. OF ACRES ASSIGNED
TO THIS WELL

40

18. DISTANCE FROM PROPOSED LOCATION*

TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

1462'

19. PROPOSED DEPTH

6200'

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

4932' GR

22. APPROX. DATE WORK WILL START*

April 1, 1997

23.

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12-1/4"	8-5/8"	24#, J-55	300'	225 sx
7-7/8"	5-1/2"	15.5#, J-55	6200'	800 sx

SEE ATTACHED EXHIBITS:

A - Surveyors Plat

B - 10 Point Plan

C - BOP Diagram


D - 13 Point Surface Use Program

E - Access Road Map

F - Production Facilities

G - Existing Wells Map

H - Pit & Pad Layout, Cuts & Fills,
Cross Sections, Rig Layout



RECEIVED
FEB 24 1997

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

Kary J. Kattenbach

TITLE Vice President

DATE February 21, 1997

(This space for Federal or State office use)

NOTICE OF APPROVAL

PERMIT NO.

APPROVAL DATE

Assistant Field Manager

APR 21 1997

APPROVED BY

[Signature]

TITLE

Mineral Resources

DATE

CONDITIONS OF APPROVAL, IF ANY:

CONDITIONS OF APPROVAL ATTACHED
TO OPERATOR'S COPY

*See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

CONDITIONS OF APPROVAL
APPLICATION FOR PERMIT TO DRILL

Company/Operator: Wildrose Resources Corporation

Well Name & Number: Federal 33-26

API Number: 43-047-32846

Lease Number: U - 36442

Location: NWSE Sec. 26 T. 8S R. 18E

NOTIFICATION REQUIREMENTS

- | | | |
|---------------------------------|---|---|
| Location Construction | - | at least forty-eight (48) hours prior to construction of location and access roads. |
| Location Completion | - | prior to moving on the drilling rig. |
| Spud Notice | - | at least twenty-four (24) hours prior to spudding the well. |
| Casing String and Cementing | - | at least twenty-four (24) hours prior to running casing and cementing all casing strings. |
| BOP and Related Equipment Tests | - | at least twenty-four (24) hours prior to initiating pressure tests. |
| First Production Notice | - | within five (5) business days after new well begins, or production resumes after well has been off production for more than ninety (90) days. |

For more specific details on notification requirements, please check the Conditions of Approval for Notice to Drill and Surface Use Program.

CONDITIONS OF APPROVAL FOR NOTICE TO DRILL

Approval of this application does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

All lease and/or unit operations will be conducted in such a manner that full compliance is made with applicable laws, regulations (43 CFR 3100), Onshore Oil and Gas Orders, and the approved plan of operations. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished the field representative to insure compliance.

Be aware fire restrictions may be in effect when location is being constructed and/or when well is being drilled. Contact the appropriate Surface Management Agency for information.

A. DRILLING PROGRAM

1. Estimated Depth at Which Oil, Gas, Water, or Other Mineral Bearing Zones are Expected to be Encountered

Report ALL water shows and water-bearing sands to Tim Ingwell of this office **prior to setting the next casing string or requesting plugging orders**. Faxed copies of State of Utah form OGC-8-X are acceptable. If noticeable water flows are detected, submit samples to this office along with any water analyses conducted.

All usable water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling, will be recorded by depth and adequately protected. All oil and gas shows will be tested to determine commercial potential.

2. Pressure Control Equipment

The BOP and related equipment shall meet the minimum requirements of Onshore Oil and Gas Order No. 2 for equipment and testing requirements, procedures, etc., for a **2M** system and individual components shall be operable as designed. Chart recorders shall be used for all pressure tests.

Test charts, with individual test results identified, shall be maintained on location while drilling and shall be made available to a BLM representative upon request.

If an air compressor is on location and is being utilized to provide air for the drilling medium while drilling, the special drilling requirements in Onshore Oil and Gas Order No. 2, regarding air or gas drilling shall be adhered to. If a mist system is being utilized then the requirement for a deduster shall be waived.

3. Casing Program and Auxiliary Equipment

Surface casing shall have centralizers on the bottom three joints, with a minimum of one centralizer per joint.

As a minimum, the usable water and oil shale resources shall be isolated and/or protected by having a cement top for the production casing at least 200 ft. above the base of the usable water zone, identified at 332 ft. or by setting surface casing to 350 ft. and having a cement top for the production casing at least 200 ft. above the shallowest potential productive zone. If gilsonite is encountered while drilling, it shall be isolated and/or protected via the cementing program.

4. Mud Program and Circulating Medium

Hazardous substances specifically listed by the EPA as a hazardous waste or demonstrating a characteristic of a hazardous waste will not be used in drilling, testing, or completion operations.

No chromate additives will be used in the mud system on Federal and Indian lands without prior BLM approval to ensure adequate protection of fresh water aquifers.

5. Coring, Logging and Testing Program

Daily drilling and completion progress reports shall be submitted to this office on a weekly basis.

All Drill Stem tests (DST) shall be accomplished during daylight hours, unless specific approval to start during other hours is obtained from the AO. However, DSTs may be allowed to continue at night if the test was initiated during daylight hours and the rate of flow is stabilized and if adequate lighting is available (i.e., lighting which is adequate for visibility and vaporproof for safe operations). Packers can be released, but tripping should not begin before daylight unless prior approval is obtained from the AO.

A cement bond log (CBL) will be run from the production casing shoe to the top of cement and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.

Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (Form 3160-4) will be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3164. Two copies of all logs, core descriptions, core analyses, well-test data, geologic summaries, sample description, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, will be filed with Form 3160-4. Samples (cuttings, fluids, and/or gases) will be submitted when requested by the AO.

6. Notifications of Operations

No location will be constructed or moved, no well will be plugged, and no drilling or workover equipment will be removed from a well to be placed in a suspended status without prior approval of the AO. If operations are to be suspended, prior approval of the AO will be obtained and notification given before resumption of operations.

Operator shall report production data to MMS pursuant to 30 CFR 216.5 using form MMS/3160.

Immediate Report: Spills, blowouts, fires, leaks, accidents, or any other unusual occurrences shall be promptly reported in accordance with the requirements of NTL-3A or its revision.

If a replacement rig is contemplated for completion operations, a "Sundry Notice" (Form 3160-5) to that effect will be filed, for prior approval of the AO, and all conditions of this approved plan are applicable during all operations conducted with the replacement rig.

The date on which production is commenced or resumed will be construed for oil wells as the date on which liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which liquid hydrocarbons are first produced into a permanent storage facility, whichever first occurs; and, for gas wells as the date on which associated liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which gas is first measured through permanent metering facilities, whichever first occurs.

Should the well be successfully completed for production, the AO will be notified when the well is placed in a producing status. Such notification will be sent by telegram or other written communication, not later than five (5) days following the date on which the well is placed on production.

Gas produced from this well may not be vented or flared beyond an initial authorized test period of 30 days or 50 MMCF following its completion, whichever occurs first, without the prior written approval of the Authorized Officer. Should gas be vented or flared without approval beyond the authorized test period, the operator may be directed to shut-in the well until the gas can be captured or approval to continue venting or flaring as uneconomic is granted and the operator shall be required to compensate the lessor for that portion of the gas vented or flared without approval which is determined to have been avoidably lost.

A schematic facilities diagram as required by 43 CFR 3162.7-2, 3162.7-3, and 3162.7-4 shall be submitted to the appropriate District Office within thirty (30) days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with 43 CFR 3162.7-4.

No well abandonment operations will be commenced without the prior approval of the AO. In the case of newly drilled dry holes or failures, and in emergency situations, oral approval will be obtained from the AO. A "Subsequent Report of Abandonment" Form 3160-5, will be filed with the AO within thirty (30) days following completion of the well for abandonment. This report will indicate where plugs were placed and the current status of surface restoration. Final abandonment will not be approved until the surface reclamation work required by the approved APD or approved abandonment notice has been completed to the satisfaction of the AO or his representative, or the appropriate Surface Managing Agency.

7. Other Information

All loading lines will be placed inside the berm surrounding the tank battery.

All off-lease storage, off-lease measurement, or commingling onlease or off-lease will have prior written approval from the AO.

Gas meter runs for each well will be located within 500 feet of the wellhead. The gas flowline will be buried or anchored down from the wellhead to the meter and within 500 feet downstream of the meter run or any production facilities. Meter runs will be housed and/or fenced.

The oil and gas measurement facilities will be installed on the well location. The oil and gas meters will be calibrated in place prior to any deliveries. Tests for meter accuracy will be conducted on new meter installations and at least quarterly thereafter. The AO will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports will be submitted to the Vernal District Office. All meter measurement facilities will conform with Onshore Oil & Gas Order No. 4 for liquid hydrocarbons and Onshore Oil & Gas Order No. 5 for natural gas measurement.

The use of materials under BLM jurisdiction will conform to 43 CFR 3610.2-3.

There will be no deviation from the proposed drilling and/or workover program without prior approval from the AO. Safe drilling and operating practices must be observed. All wells, whether drilling, producing, suspended, or abandoned will be identified in accordance with 43 CFR 3162.

"Sundry Notice and Report on Wells" (Form 3160-5) will be filed for approval for all changes of plans and other operations in accordance with 43 CFR 3162.3-2.

Section 102(b)(3) of the Federal Oil and Gas Royalty Management Act of 1982, as implemented by the applicable provisions of the operating regulations at Title 43 CFR 3162.4-1(c), requires that "not later than the 5th business day after any well begins production on which royalty is due anywhere on a lease site or allocated to a lease site, or resumes production in the case of a well which has been off production for more than 90 days, the operator shall notify the authorized officer by letter or sundry notice, Form 3160-5, or orally to be followed by a letter or sundry notice, of the date on which such production has begun or resumed."

If you fail to comply with this requirement in the manner and time allowed, you shall be liable for a civil penalty of up to \$10,000 per violation for each day such violation continues, not to exceed a maximum of 20 days. See Section 109(c)(3) of the Federal Oil and Gas Royalty Management Act of 1982 and the implementing regulations at Title 43 CFR 3162.4-1(b)(5)(ii).

The APD approval is valid only until September 30, 1996 unless production is established from another well within the lease prior to that date. If production in paying quantities is established prior to that date then the APD is valid for a period of one (1) year from the signature date. An extension period may be granted, if requested, prior to the expiration of the original approval period, if production in paying quantities has been established from another well from within the lease hold.

In the event after-hours approvals are necessary, please contact one of the following individuals:

Ed Forsman (801) 789-7077
Petroleum Engineer

Wayne P. Bankert (801) 789-4170
Petroleum Engineer

Jerry Kenczka (801) 781-1190
Petroleum Engineer

BLM FAX Machine (801) 781-4410

EPA'S LIST OF NONEXEMPT EXPLORATION AND PRODUCTION WASTES

While the following wastes are nonexempt, they are not necessarily hazardous.

Unused fracturing fluids or acids

Gas plant cooling tower cleaning wastes

Painting wastes

Oil and gas service company wastes, such as empty drums, drum rinsate, vacuum truck rinsate, sandblast media, painting wastes, spent solvents, spilled chemicals, and waste acids

Vacuum truck and drum rinsate from trucks and drums, transporting or containing nonexempt waste

Refinery wastes

Liquid and solid wastes generated by crude oil and tank bottom reclaimers

Used equipment lubrication oils

Waste compressor oil, filters, and blowdown

Used hydraulic fluids

Waste solvents

Waste in transportation pipeline-related pits

Caustic or acid cleaners

Boiler cleaning wastes

Boiler refractory bricks

Incinerator ash

Laboratory wastes

Sanitary wastes

Pesticide wastes

Radioactive tracer wastes

Drums, insulation and miscellaneous solids.

SURFACE USE PROGRAM
Conditions of Approval (COA)

-Access roads and surface disturbing activities will conform to standards outlined in the Bureau of Land Management and Forest Service publication: Surface Operating Standards for Oil and Gas Exploration and Development, (1989).

The road shall be constructed/upgraded to meet the standards of the anticipated traffic flow and all-weather road requirements. Construction/upgrading shall include ditching, draining, and crowning (2 to 3%). Graveling or capping the roadbed will be required as necessary to provide a well constructed safe road. Prior to construction/upgrading, the proposed road surface or existing road shall be cleared of any snow cover and allowed to dry completely. Traveling off the 30 foot right-of-way will not be allowed. Should mud holes develop, they shall be filled in to prevent detours. Road drainage crossings shall be of the typical dry creek drainage crossing type. Crossings shall be designed so they will not cause siltation or accumulation of debris in the drainage crossing nor shall the drainages be blocked by the roadbed. Erosion of drainage ditches by runoff water shall be prevented by diverting water off at frequent intervals by means of cutouts. Upgrading shall not be allowed during muddy conditions. When snow is removed from the road during the winter months, the snow should be pushed outside of the burrow ditches and the turn outs should be kept clear so that when the snow melts the water will be channeled away from the road.

METHODS FOR HANDLING WASTE MATERIALS AND DISPOSAL

The reserve pit shall be lined with a synthetic liner that is a minimum of 12 mil thickness with sufficient bedding to cover any rocks. The liner will overlap the pit walls and be covered with dirt and/or rocks to hold it in place. No trash, scrap pipe, etc., that could puncture the liner will be disposed of in the pit.

Plans For Reclamation Of Location

At time of final abandonment the intent of reclamation will be to return the disturbed area to near natural conditions. Recontour the surface of the disturbed area to **blend all cuts, fills, road berms, and borrow ditches to be natural in appearance** with the surrounding terrain. After recontouring of the area any stockpiled topsoil will be spread over the surface, and the area reseeded and revegetated to the satisfaction of the authorized officer of the BLM. Contact the authorized officer of the BLM at the time of reclamation for the required seed mixture.

DIVISION OF OIL, GAS AND MINING

SPUDDING INFORMATION

CONFIDENTIAL

Name of Company: WILDROSE RESOURCES

Well Name: FEDERAL 33-26

Api No. 43-047-32846

Section: 26 Township: 8S Range: 18E County: UINTAH

Drilling Contractor UNION

Rig # 17

SPUDDED:

Date 5/15/97

Time 5:30 PM

How ROTARY

Drilling will commence _____

Reported by CARY KALTENBACHER

Telephone # 1-801-828-7513

Date: 5/19/97 Signed: C. DANIELS

OPERATOR Wildrose Resources Corp.OPERATOR ACCT. NO. N 9660ADDRESS 4949 S. Albion St.Littleton, CO 80121


ACTION CODE	CURRENT ENTITY NO.	NEW ENTITY NO.	API NUMBER	WELL NAME	WELL LOCATION					SPUD DATE	EFFECTIVE DATE
					QQ	SC	TP	RG	COUNTY		
A	99999	12127	43-047-32846	Federal 33-26	NW/SE	26	85	18E	Uintah	5/15/97	
WELL 1 COMMENTS: <i>Entity added 5-28-97. yec</i>											
WELL 2 COMMENTS:											
WELL 3 COMMENTS:											
WELL 4 COMMENTS:											
WELL 5 COMMENTS:											

ACTION CODES (See instructions on back of form)

- A - Establish new entity for new well (single well only)
- B - Add new well to existing entity (group or unit well)
- C - Re-assign well from one existing entity to another existing entity
- D - Re-assign well from one existing entity to a new entity
- E - Other (explain in comments section)


NOTE: Use COMMENT section to explain why each Action Code was selected.

(3/89)



Kary Kattenbach
Signature
V.P.
Title
5/15/97
Date
Phone No. 303,770-6566

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT



FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS, SOIL, GAS & MINING

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other Dry

2. Name of Operator

Wildrose Resources Corp. 303-770-6566

3. Address and Telephone No.

4949 S. Albion St, Littleton, CO 80121

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FEL (NW/SE)

Section 26, T8S, R18E

5. Lease Designation and Serial No.

U-36442

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Federal 33-26

9. API Well No.

43-047-32846

10. Field and Pool, or Exploratory Area

8 mile Flat North

11. County or Parish, State

Uintah County, Utah

CONFIDENTIAL

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged on may 23, 1997 as follows:

Plug #1: 4930'-4615' 100 sx class 'G' w/ 1% CaCl₂.
WOC 3 hrs. Tagged plug @ 4655'.

Plug #2: 1910'-1650' 80 sx class 'G' w/ 2% CaCl₂.
Hole stayed full after pumping plug.

Plug #3: 472'-272' 80 sx class 'G' w/ 3% CaCl₂.
Hole stayed full after pumping plug.

Plug #4: 53' - 0' 20 sx class 'G' w/ 3% CaCl₂
Cement at surface.

Dry hole marker is installed. Rehab will be done in the fall.

14. I hereby certify that the foregoing is true and correct

Signature Kaltenbach

Title V.P.

Date 6/5/97

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL ☐ WELL ☐ GAS ☐ WELL ☐ DRY ☒ Other _____

b. TYPE OF COMPLETION:
NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____

2. NAME OF OPERATOR

Wildrose Resources Corp.

3. ADDRESS OF OPERATOR

4949 S. Albion St., Littleton, CO 80121

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1980' FSL & 1980' FEL (NW/SE)

At top prod. interval reported below same

At total depth same

CONFIDENTIAL

14. PERMIT NO. 43-047-32846 DATE ISSUED

5. LEASE DESIGNATION AND SERIAL NO.

U-36442

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal

9. WELL NO.

33-26

10. FIELD AND POOL, OR WILDCAT

8 mile Flat North

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 26, T8S, R18E

12. COUNTY OR PARISH

Dinteh

13. STATE

Utah

15. DATE SPUDDED 5/15/97 16. DATE T.D. REACHED 5/22/97 17. DATE COMPL. (Ready to prod.) 5-23-97 PJA 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 4932' GR 19. ELEV. CASINGHEAD 4932'

20. TOTAL DEPTH, MD & TVD 6320' 21. PLUG, BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY* 23. INTERVALS DRILLED BY 0'-TD 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* N/A 25. WAS DIRECTIONAL SURVEY MADE No

26. TYPE ELECTRIC AND OTHER LOGS RUN

DLL, SDL, DSN 6-20-97

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well!)

CASINO SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8	24	376	12 1/4	200 SX (To Surface)	—

CONFIDENTIAL

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
N/A					N/A		

31. PERFORATION RECORD (Interval, size and number)

N/A

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED

33.* PRODUCTION

DATE FIRST PRODUCTION PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) WELL STATUS (Producing or shut-in)

DATE OF TEST HOURS TESTED CHOKE SIZE PROD'N. FOR TEST PERIOD OIL—BBL. GAS—MCF. WATER—BBL. GAS-OIL RATIO

FLOW. TUBING PRESS. CASING PRESSURE CALCULATED 24-HOUR RATE OIL—BBL. GAS—MCF. WATER—BBL. OIL GRAVITY-API (CORR.)

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

35. LIST OF ATTACHMENTS

Logs, Daily Reports

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Kang Keltner Lee TITLE V.P.

DATE 6/12/97

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
			CONFIDENTIAL	Green River Douglas Creek Wasatch Tongue of Green River	1777' 5067' 6205'	1777' 5067' 6205'

DAILY DRILLING REPORT

Operator: Wildrose Resources Corporation
Well: Federal #33-26
T 8 S, R 18 E, Section 26
NW SE (1980' FSL & 1980' FEL)
Uintah County, Utah
Projected TD - 6200'
Elevation: GR: 4931', KB: 4941' estimated
Contractor: Union Drilling Company #17

05/16/97 Day 1: TD-362' drilling surface hole. MI & RU Union Rig #17.
Spudded @ 5:30 PM 5/15/97.

05/17/97 Day 2: TD-768' drlg. Drilled 406' in 8 3/4 hrs w/ air/foam.
Finished drilling 12 1/4" surface hole to 400'. Ran 9 jts (366') 8 5/8". 24#,
J-55, STC csg w/ guide shoe, insert float, and 3 centralizers. Set csg @ 376'
KB. RU HOWCO. Pumped 10 BW & 20 bbl gel water. Cemented w/ 200 sx Class 'G'
w/ 2% CaCl2 & 1/4# /sk Flocele. Displaced w/ 21 BW. Plug down @ 8 AM 5/16/97.
Had good cement to surface. WOC. NUBOP's. Tested BOP to 2000 psi & csg to
1500 psi. Ran Bit #3 has drld 368' in 6 hrs. Survey: 1/2 @ 600'.

05/18/97 Day 3: TD-1990' drlg. Drld 1222' in 23 hrs w/ air/foam. Bit #3 has
drld 1590' in 29 hrs. Surveys: 3/4 @ 1100'. 1/2 @ 1550'.

05/19/97 Day 4: TD-3071' drlg. Drld 1081' in 22 1/4 HR w/ air/foam. Bit #3
has drld 2671' in 51 1/4 hrs. Surveys: 1/2 @ 2000', 1 @ 2550', 1 1/4 @
3050'.

05/20/97 Day 5: TD-4196' drlg. Drld 1125' in 22 1/4 hrs w/ air/foam. Bit #3
has drld 3796' in 73 1/2 hrs. Surveys: 1 1/4 @ 3550', 1 1/2 @ 4050'.

05/21/97 Day 6: TD-4934' drlg. Drld 783' in 18 1/4 hrs w/ 2% KCl
substitute. Pulled Bit #3 @ 4509'. Bit #3 drld 4109' in 84 3/4 hr. Ran Bit #4,
7 7/8" SEC 33 w/ mud motor @ 4509'. Bit #4 has drld 425' in 7 hrs. Survey: 1
@ 4500'.

05/22/97 Day 7: TD-5920' drlg. Drld 986' in 21 1/2 hrs w/ 2% KCl
substitute. Bit #4 has drld 1411' in 28 1/2 hrs. Surveys: 1 @ 5000 1, 1 1/4
@ 5500'.

05/23/97 Day 8: TD-6320'. RU HOWCO tp plug. Drld 400' in 8 hrs w/ 2% KCl
substitute. Reached TD @ 12:45 PM 5/22/97. LDDP. Bit #4 drld 1811' in 36 1/2
hrs. Ran logs using Halliburton as follows:

DLL 6275' - 377'

SDL/DSN 6275' - 4000'

Logger's TD 6325'. Pick up 4930' drill pipe.

05/24/97 Day 9: TD-6320'. P & A'd. Circulated for 1 1/4 hrs. Plugged as
follows:

Plug #1: 4930'-4515': 100 sx Glass 'G' w/ 1% CaCl2. Pulled 10
stds. Waited 3 hrs. Ran 6 stds - tagged cement @ 4655'. Laid down 97 jts DP.

Plug #2: 1910'-1650': 80 sx Class 'G' w/ 2% CaCl2. Pulled 7 stds
DP. Filled hole - stayed full. LD 46 jts DP.

Plug #3: 472'-272': 80 sx Class 'G' w/ 3% CaCl2. LD 13 jts. Filled
hole - stayed full. NDBOP's. Ran 2 jts DP to 63'.

Plug #4: 53'-0': 20 sx Class 'G' w/ 3% CaCl2. Released rig @ 7 AM
5/23/97.